



5043 Farlin Ave.
St. Louis, MO 63115
www.associatedequip.com
314-385-5178

Product Bulletin

MODEL 9425

**20 Amp / 25 Amp Peak
Output Bench Charger /
Power Supply for
Standard Automotive,
Deep-Cycle, AGM and
Gel Cell batteries**



Specifications:

Model Number	9425
DC Output	20 Amps
DC Leads	6 ½' 10 AWG
Clamp Rating	300A
Limited Warranty	One Year
Shipping Dimensions	14"x12"x12"
Weight	21 LBS
AC Cord / Voltage	6' 18-3 / 120VAC 60 Hz
Battery Types	12 Volt Flooded, AGM, and Gel Cell batteries - including Spiral Cell, Orbital, or Optima batteries
Display	3 LED display indicating charge status

Features:

- **Electrical Stability System (ESS™)** technology turns 9425 into a stable power supply for extended service procedures or re-flashes. Nominal 13.7V DC Output
- Program for deep discharge recovery of flooded batteries
- Patented diagnostics indicate weak or defective battery
- Charges all types of 12 volt batteries.
- Designed for AGM, Gel Cell, Sealed, and Standard Flooded batteries including Spiral Cell, Orbital, or Optima batteries
- **MADE IN USA**