

5043 Farlin Ave
 St. Louis, MO 63115
 www.associatedequip.com

Model 6027B 6/12/24 Volt Wheel Charger Safe for Standard Lead Acid and Maintenance Free Batteries

6027B Features

- 230 VAC; 50/60 HZ electrical requirements
- 90/75/55 Amp continuous rating
- Multi-diode rectifiers (patented) to take over in case of failure
- Fan cooling mechanism prevents overheating enhancing unit's life span significantly
- CSA listed with "Safe in Any Weather" operation
- Will not arc or spark
- Patented "Flexi-Spring" cable guards relieve cable stress
- Heavy-duty chrome plated handle
- CE approved:
 - Tested for Safety by TUV Rheinland of North America
 - Tested for EMC by DLS Electronic Systems
- 3-Year limited warranty on transformer and rectifier

MADE IN THE USA



UL or CSA Continuous Rating	Crank Assist	Operating Charging Voltage	Battery Types	Indoor/Outdoor Rated	DC Cable Length and Gage	Clamp Rating	A/C Cord Length	Weight (Pounds) Lbs	Dimensions (LxWxH)
90/75/55a	500A	6/12/24V	SLA	Y	8' 4AWG	500A	8' 230VAC	75	15.5x19x21.5"