



5043 Farlin Ave.
St. Louis, MO 63115
www.associatedequip.com
314-385-5178

Product Bulletin

MODEL 9525A & 9525X
International

**20 Amp / 25 Amp Peak
Output Bench Charger /
Power Supply for
Standard Automotive,
Deep-Cycle, AGM and
Gel Cell batteries**



9525A



9525X

Specifications:

Model Number	9425A & 9425X
Electrical Requirements	240V-2A
Continuous Ratings	20A
Clamp Rating	300A
DC Leads	6.2' 10 AWG
Shipping Dimensions	12"x12"x14"
Weight	21 LBS
AC Cord / Voltage	6' 18-3
Battery Types	12 Volt Flooded, AGM, and Gel Cell batteries - including Spiral Cell, Orbital, or Optima batteries
Display	3 LED display indicating charge status

Features

- Micro-processor controlled and fully automatic charging of flooded batteries including GEL and AGM
- Analyzes battery condition and automatically selects proper charging technique
- Electrical Stability System (ESS™) technology feature is a stable power supply for extended service procedures or re-flashes, Nominal 13.9V DC output
- Model 9525A – AC Plug Continental Europe, Latin America & Middle East
- Model 9525X – AC Plug for China
- Program for deep discharge recovery of flooded batteries
- Patented diagnostics indicate weak or defective battery
- Utilizes three color LEDs to monitor charging status
- Switch for selecting battery type
- Dead Battery Override Control
- Maintains battery charge, can be left connected to battery