BASSOCIATED

5043 Farlin Ave St. Louis, MO 63115

www.associatedequip.com

Model ESS6011

12/24V Intellamatic® Wheel Charger/Analyzer & Power Supply with Dead Battery Override

ESS6011 Features

- 70 Amp continuous rating in Power Supply Mode
- Electrical Stability System (ESS™) technology turns ESS6011 into a stable power supply for extended service procedures or re-flashes.
 Nominal 13.7V DC Output
- Program for deep discharge recovery of flooded batteries
- Patented diagnostics indicate weak or defective battery
- Designed for AGM, Gel Cell, Sealed, and Standard Flooded batteries including Spiral cell, OrbitalTM, or OptimaTM Batteries
- Dead Battery Override Control
- "Safe In Any Weather" Operation
- UL Listed
- 3-Year limited warranty
- MADE IN THE USA



UL or CSA Continuous Rating	Crank Assist	Operating Charging Voltage	Battery Types	Indoor/Outdoor Rated	DC Cable Length and Gage	Clamp Rating	A/C Cord Length	Weight (Pounds) Lbs	Dimensions (LxWxH)
70/35A	270A	12/24V	SLA, AGM, Gel-Cell	Y	6' 1/2 AWG	500A	6' 16-3	49	17.25X16.5X26.5